

# MAX

FAST AND VERSATILE. THE MAX.



The Schechtl MAX is perfect where there is extensive work to be done on roofs and exteriors. With a range of control systems and backgauge options as well as a wide selection of rails, the MAX can be fully customised to suit your wishes.

## BENEFITS

- ✓ Ideal for high workloads
- ✓ Short bending times through extremely high swivel speed
- ✓ Time-saving through **1-man operation**
- ✓ **Minimal maintenance effort**
- ✓ **Versatile** through a comprehensive range of accessories

## TECHNICAL DATA

Subject to change

MODEL	MAX		400	310	250
<b>WORKING LENGTH</b>		mm	4040	3100	2540
<b>OUTPUT</b>	Steel (400N/mm <sup>2</sup> )	mm	1,00	1,50	2,00
	Stainless steel (600N/mm <sup>2</sup> )	mm	0,60	1,00	1,25
	Cooper (300N/mm <sup>2</sup> )	mm	1,00	2,00	2,50
	Aluminium (250N/mm <sup>2</sup> )	mm	1,50	2,00	3,00
	Zinc (150N/mm <sup>2</sup> )	mm	2,00	3,00	3,50
<b>DIMENSIONS</b>	Length	mm	5147	4207	3647
	Depth	mm	1842	1842	1842
	Overall height	mm	1745	1745	1745
<b>WEIGHT</b>		kg	3600	3100	2800
<b>CLAMPING BEAMS</b>	Opening height	mm	140	140	140

# CONTROLS

TheMAXis available with the following controls.

- ✓ ST
  - ✓ CNC S-Touch
  - ✓ ECT
- 

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Sharp rail 20° R 1 mm offset
  - ✓ Insert rail 10 mm
  - ✓ Insert rail 24 mm
  - ✓ Motorized backgauge 6-750 mm
  - ✓ Motorized backgauge 6-1000 mm
  - ✓ Foot switch
  - ✓ two foot switches
- 

# ADD-ONS - OPTIMISE YOUR MAX

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear RSL
  - ✓ Manual back gauge 750 mm
  - ✓ Conical backgauge fingers
  - ✓ PC offline software
  - ✓ Advice on rails
  - ✓ Advice on backgauges
- 

All details onMAX