

# TBX

MANOEUVRABLE AND MOBILE. THE TBX.



With a working length of 1000 mm, the Schechtl TBX is the smallest of our manual swivel bending machines. Its compact size makes it ideal for one-day job sites as well as for working on roofs and on scaffolding. The TBX can be installed on a workbench or in a construction vehicle. With the optional X-shaped support stand, the TBX can be quickly folded and pulled behind you like a roller suitcase.

## BENEFITS

- ✓ **Practical:** Particularly small and handy
- ✓ **Flexible:** Easy installation on any workbench or in a van
- ✓ **Mobile:** Fold the machine with the X-shaped support stand and pull it behind you like a roller suitcase
- ✓ **Wear-free** and maintenance-free roller bearings
- ✓ **Reliable:** Crownable bending beam – always the right pretension for the material type and thickness

## TECHNICAL DATA

Subject to change

<b>MODEL</b>	<b>TBX</b>		100
<b>WORKING LENGTH</b>		mm	1000
<b>OUTPUT</b>	Steel (400N/mm <sup>2</sup> )	mm	0,80
	Stainless steel (600N/mm <sup>2</sup> )	mm	0,50
	Cooper (300N/mm <sup>2</sup> )	mm	1,00
	Aluminium (250N/mm <sup>2</sup> )	mm	1,00
	Zinc (150N/mm <sup>2</sup> )	mm	1,00
<b>DIMENSIONS</b>	Length	mm	1240
	Depth	mm	692
	Overall height	mm	1150
<b>WEIGHT</b>		kg	38
<b>CLAMPING BEAMS</b>	Opening height	mm	45

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Clamping beam rail 45° R 1 mm
- 

# ADD-ONS - OPTIMISE YOUR TBX

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
  - ✓ X-shaped support stand
  - ✓ Beading apparatus
- 

All details onTBX