

UK

YOUR MULTI-TALENTED MACHINE. THE UK.



The Schechtl UK handles the production of special shapes, box and cassette forms and adjustment tasks. It can bend up to 1.50 mm steel and is available in working lengths 1 m and 1.25 m. The comprehensive range of standard equipment and many extension options make the UK a real multi-tool.

BENEFITS

- ✓ Segments with the original Schechtl **quick clamping system**
- ✓ **Tool-free adjustment** of all segments supplied in the 3 areas lower, bending and clamping beam (Standard height of all segments 100 mm)
- ✓ **Bending angle limitation** for uniform, recurring bending operations
- ✓ Quick, tool-free adjustment of the **clamping beam clamping pressure**
- ✓ Tool-free adjustment of the **bending beam lowering**
- ✓ Foot pedal for **free-hand clamping** of the workpiece
- ✓ **Practical:** storage tray for the segments
- ✓ **Storage box** for accessories and tools that also serves as a sheet support
- ✓ 4 swivel castors with locking brake for **mobile use** in the workshop

TECHNICAL DATA

Subject to change

| MODEL | UK | | 125 | 100 |
|-----------------------|---|----|------|------|
| WORKING LENGTH | | mm | 1250 | 1000 |
| OUTPUT | Steel (400N/mm ²) | mm | 1,25 | 1,50 |
| | Stainless steel (600N/mm ²) | mm | 0,80 | 1,00 |
| | Cooper (300N/mm ²) | mm | 1,50 | 2,00 |
| | Aluminium (250N/mm ²) | mm | 2,00 | 2,25 |
| | Zinc (150N/mm ²) | mm | 2,00 | 2,00 |
| DIMENSIONS | Length | mm | 1730 | 1480 |
| | Depth | mm | 740 | 740 |
| | Overall height | mm | 1180 | 1180 |
| WEIGHT | | kg | 290 | 260 |
| CLAMPING BEAMS | Opening height | mm | 96 | 96 |

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Segments with quick clamping system
- ✓ Clamping beam pressure setting
- ✓ Bending beam lowering
- ✓ Bending beam stop
- ✓ Storage box
- ✓ Foot pedal
- ✓ Castors

ADD-ONS - OPTIMISE YOUR UK

The following add-ons are possible depending on the version (working length/control):

- ✓ Clamping beam segments in R 2 mm
- ✓ Clamping beam segments in R 3 mm
- ✓ Clamping beam segments 140 mm high
- ✓ Clamping beam segments 160 mm high
- ✓ Back gauge 1000 mm
- ✓ Universal backgauge table UA125
- ✓ Windowsill insert, standard
- ✓ Windowsill insert, variable (6-part)

All details onUK